


Technical Data Sheet	Title: Andywrap® Carpet Film	
Issue Number: 17	Dated: January 2025	

Product Description

Clear LDPE virgin material with 30% recycled content carpet protection film coated with water based acrylic adhesive, supplied individually boxed or bulk

Applications

Temporary protection for carpets, mosquettes and sensitive surfaces against dirt & damage.

Features & Benefits

Protects against decorating spills & dirt during building works, remodelling.

Heavy duty rip resistant material.

High foot traffic when moving house & parties

Suitable for use on stair,

Fast installation & removal.

Self-adhesive for secure positioning

Technical Performance


Description	Units	Value
Substrate		LDPE
Total Thickness	mm	0.05mm ± 10%
Colour		Transparent
Density	g/cm ³	0.925
Tensile Strength (MD)	N/25mm	>15
Tensile strength (CD)	N/25mm	>10
Adhesion to stainless steel	g/25mm	500g/25mm ± 10%
Static shear 23°C	hours	>48
Elongation at break (MD)	%	>200
Elongation at break (CD)	%	>350

Declaration of Conformity Information

Classification Bfl-s1

Complies with European Directive 305/2011/EEC (Construction products Directive) 2011/65/EU (REACH) Tests performed according to the relevant sections of EN 13051-1 2007 +A1:2009 EN ISO 9239-1:2010

The information supplied is accurate to the best of Andywrap Eurofilm Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising.

Technical Data Sheet	Title: Andywrap® Carpet Film	
Issue Number: 17	Dated: January 2025	

REACH SVHC Status

NO SHVC present according to candidates list of the **UK 25/06/20 & EU 07/11/24**

RoHS 1 2&3 Compliance Status


(RoHS1) Directive 2002/95/EC & (RoHS2) EU 2015/863 amending Annex II to Directive **(RoHS3) 2011/65/EU** of the European Parliament and of the Council as regards the list of restricted substances.

Storage Details - Store in dry conditions in its original packaging

Fire Classification Information

All national fire classifications in the countries of European Union have been superseded by Euro classes Bfl-s1 and Cfl-s1 (fire-retardant) According to EN 13501-1, which are now binding in the European Union. Fl=Flooring S=Smoke, This European standard for the fire classification of construction products according to their reaction of fire tests lays down these new classes for the flammability of floor covering, which are now applicable throughout Europe for the first time. The “CE mark” for floor covering specifies the testing or classification of flammability according to EN 13501-1, whereby this must be confirmed by a declaration of conformity. This mark indicates that according to the manufacturer, a product satisfies the essential requirements of the corresponding harmonised European standards and can be freely traded across boundaries in EU territory. EN 13501-1 specifies the methods to be used for classifying the flammability of construction products. The testing of floor covering differs from that of customary construction products and is described separately in this standard. This standard will supersede the national standards for the flammability of floor covering still applicable in the individual EU countries.

The information supplied is accurate to the best of Andywrap Eurofilm Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising.

Technical Data Sheet	Title: Andywrap® Carpet Film	
Issue Number: 17	Dated: January 2025	

Application Guidelines

Applications Notes

1. Before applying the film ensure the surface is clean & dry.
2. Customers must fully evaluate the product by testing prior to using. Test the film for 48 hours on a small hidden area of carpet to ensure compatibility with the particular carpet and to ensure there is no adhesive transfer on the carpet.
3. To apply the roll, lay it on the floor facing the direction required to cover. Push the roll forward a small distance and press down firmly to ensure the film has adhered to the carpet.
4. Continue to unroll, pressing down and smoothing out any air pockets, checking the film is rolled straight.

Limitations

1. Do not leave the film on carpet for longer than 30days.
2. For use on Synthetic Carpets Only.
3. Film is one time use only. Remove and dispose of in accordance with local environmental regulations.
4. Do not use on wool or oriental carpets. Not suitable for use on rugs, worn carpets, or loose fitted carpet tiles.
5. Do not use on hard surfaces, such as hardwood, ceramic tile, linoleum, vinyl flooring or marble.
6. Do not apply on newly laid carpets where a glue or adhesive has been used. Allow up to 72 hours for any vapours to evaporate before laying the film.
7. Do not apply to a damp surface which will prevent any moisture from evaporating and could cause discoloration of carpet fibres.
8. If carpet has been recently cleaned, allow it to completely dry for a minimum of 10 days before using the film.
9. High traffic areas or outdoor exposure may require renewal of film weekly.
10. The product should be stored no longer than 6months at room temperature.
11. Check for adhesive transfer on a regular basis.

The information supplied is accurate to the best of Andywrap Eurofilm Ltd knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising.