

TECHNICAL SPECIFICATION

WORKING AT HEIGHT



Spartan™ 2m Adjustable Single Fall Arrest Lanyard

Spartan™ 2m Adjustable Fall Arrest Lanyard / Code: FAR0310



DESCRIPTION

Webbing lanyard, adjustable from 1.45m to 2m, with integral shock absorber. The lanyard is made from 30mm wide polyester webbing with steel karabiner connector and steel scaffold hook, and features a fall indicator on the energy absorber.

OPTIONS

Spartan™ 2m Adjustable Fall Arrest Lanyard (FAR0310)

DOWNLOADS

 [Image Pack \(ZIP\)](#)



COMPATIBLE PRODUCTS

1m Webbing Anchorage Sling
Aerialine™ 20m Horizontal Lifeline
2m Steel Cable Anchorage Sling
2m Webbing Anchorage Sling
K2™ 2-Point Harness
K2™ 3-Point Harness
K2™ 5-Point Harness
Pioneer™ 2-Point Harness
Pioneer™ 2-Point QR Harness
Pioneer™ 2-Point Rescue Harness
Pioneer™ 3-Point Harness
Spartan™ 1-Point Harness
Spartan™ 2-Point Harness
Spartan™ 3-Point Harness

ACCESSORIES

Aluminium Scaffolding Hook
Aluminium Tower Hook
Aluminium Triple Lock Karabiner
Aluminium Twist Lock Karabiner
Steel Screw Gate Karabiner
Steel Twist Lock Karabiner

SAFETY STANDARDS

EN 355

SPECIFICATIONS

Fall Indicator

Yes

Length

Adjustable up to 2m

Material

30mm Wide Polyester Webbing With Textile Loops On Both Ends

Shock Absorber

External

Sharp Edge

No

Rope Ends

X

Protective Rope Sleeve

No

Adjustment Device

Manual Ring Type Adjuster Of Forged Alloy Steel



Product Weight

1350g

Delivered With

1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 1 Alloy Steel Scaffold Hook. Gate Opening 50mm. Conforms to EN362 Class T.

APPLICATIONS

Leading Edge

RANGE

FALL ARREST LANYARDS

